


PROFIBUS



Design

Wire

Bare copper wire ø 1.05 mm (0,041 in)
 Insulation of foamed Polyethylene (PE) with skin ø 2.55 mm (0,100 in)

Core

2 wires, RD and GN twisted to a pair
 Plastic tape, overlapped
 Inner-Jacket Polyvinylchloride (PVC) ø 5.4 mm (0,213 in)
 Alulaminat foil overlapped, applied longitudinally
 Shield braiding of tinned copper wires 0.15 mm dia
 Coverage about 90% ø 6.2 mm (0,244 in)

Jacket

Polyvinylchloride (PVC) BU
 Wall thickness about 0.9mm ø (8.0 ±0.4) mm (0.315 ±0.016 in)

Printing: "sequential length in metres" BizLink Special Cables Germany PROFIBUS FMS ES L45467-J20-C275
 * 18AWG (SHIELDED) (UL) E119100 CM 75°C or CL3 or AWM 21694 600V SUN RES OIL RES I *
 "internal lot number"
 Textintervals about 1000 mm

Electrical data at 20°C

Conductor resistance	≤	22	Ohm/km
Insulation resistance	≥	10	MOhm*km
Capacitance (1 kHz wire/wire)	≈	50	nF/km
Capacitance (1 kHz wire/screen)	≈	92	nF/km
Operating voltage		100	V
UL-Rating		600	V
Test voltage (wire/wire/screen rms 50Hz 1 min)		2000	V
Characteristic Impedance (31.25 KHz)		(100 ±20)	Ohm
Attenuation (39 KHz)	≤	3	dB/km
Capacitance unbalance e	≤	2	nF/km
Inductance (31.25 KHz)		650	µH/km
Surface transfer impedance (20 MHz)	≤	5	mOhm/m
rel. velocity of propagation	≈	81	%

CONFIDENTIALITY: This document and its content must be treated strictly confidential and are property of BizLink Special Cables Germany GmbH

Mechanical and thermal characteristics

Conductor material acc. to DIN EN 13602 Cu-ETP-A...

Screen material acc. to DIN EN 13602 Cu-ETP-A...-B

Insulating material acc. to DIN EN 50290-2-23 (VDE 0819), table 2/A (HD 624.3)

Jacket material acc. to DIN VDE 0207, compound type YM5

Oil resistant acc. to UL 758 Sec. 15 (60°C)

Flame retardant acc. to UL 1685 (Vertical tray) CM

Sunlight resistant acc. to UL 1581 Sec.1200

Leakage test according to EN 60079-14 annex E

File E119100 Vol.1 Sec.16 Page 6 (CM)

File E116441 Vol.1 Sec.6 Page 6 (CL3)

UL STYLE 21694

Application / Special feature:

Flame retardant acc. to IEC 60332-1-2

Permissible temperature range : -20 °C (-4 °F) up to 80 °C (176 °F)

Min. bending radius allowed : repeated 10X \varnothing , single 5X \varnothing

Tensile strength \leq 150 N

PVC weight with Phthalate : 47.4 Kg/km

PVC weight without Phthalate : 0.0 Kg/km

Weight about : 98 kg/km (65,7 lb/1000ft)

Designation of order

L45467-J20-C275

228887

02YSY(ST)CY 1X2X1.0/2.55-100 BL OE FR

1000 m (3281 ft) on non-returnable reel

Product has not been tested and classified according to the CPR (EU/305/2011).
The product shall not be permanently installed in buildings in the EU.