

# GigaLine<sup>®</sup> A-DQ(ZN)B2Y - PVP

## Outdoor cable, stranded loose tube, 6000 N

2 x 12 E9/125/250 OS2 G652.D/G657.A1



Illustration similar

### Description

Exterior fiber-optic cable with stranded loose tube, longitudinally watertight, with metal free rodent protection

### Properties / applications

Outdoor cable with metall free rodent protection for fixed installation, layable directly in the ground.

Suitable for campus/ backbone cabling and for the use in generic cabling acc. to ISO/IEC 11801 and EN 50173. Ideally suited for all applications of Classes OF 300 to OF 10000 (depending on the fiber).

### Laying

Outdoors, pulling in or air blown installation into pipes and directly into the ground (sand bed). For automated cable pulling with cable winches the use of tensile-force-recording equipment is obligatory.

### Construction

Fiber colours	IEC 60304: Fiber 1-12: Red, green, blue, yellow, white, grey, brown, violet, turquoise, black, orange, pink. Fiber 13-24: Red, green, blue, yellow, white, grey, brown, violet, turquoise, transparent, orange, pinke, each with black ring marking, except transparent.
Tube type	Stranded filled loose tube
Core colours	1st tube red, 2nd white, others yellow (9/125)
Strain relief (in total)	Non metallic, glass rovings
Outer sheath	Polyethylene, UV resistant
Colour	Jet black
Cable marking	KERPEN DATACOM GmbH GigaLine A-DQ(ZN)B2Y \$Abmessung\$ \$Fasertyp\$ 6000N \$2xWechselstromsymbol \$ \$TrommelNr.\$ \$m-sign.\$

# GigaLine<sup>®</sup> A-DQ(ZN)B2Y - PVP

## Outdoor cable, stranded loose tube, 6000 N

2 x 12 E9/125/250 OS2 G652.D/G657.A1

### Optical characteristics

Category	OS2 G652.D/G657.A1
Fiber type	E9/125/250
Dispersion	@ 1310 nm max. 3.5 ps/(nm x km) @ 1550 nm max. 18 ps/(nm x km)
Attenuation	@ 1310 nm max. 0.36 dB/km @ 1383 nm max. 0.36 dB/km @ 1550 nm max. 0.22 dB/km @ 1625 nm max. 0.22 dB/km

### Mechanical characteristics (cable)

Bending radius (static) (min.)	15x outer-Ø
Bending radius (dynamic) (min.)	20x outer-Ø
Max. strain relief	6000 N
Crush resistance (short term)	8000 N/100mm
Crush resistance (long term)	3000 N/100mm

### Thermal characteristics (cable)

Temperature (transport / storage)	-40 °C up to +70 °C
Temperature during installation	-10 °C up to +50 °C
Temperature after installation	-40 °C up to +60 °C

### Standards, certificates and approvals

Fibre standard	ISO/IEC 11801 OS2 ITU-T G652.D ITU-T G657.A1 IEC 60793-2 B1.3
Cabling standard	EN 50173, ISO/IEC 11801
Fire class	-
Halogen-free	IEC 60754-1
Long. watertightn.	IEC 60794-1-2 F5
Quality seal with production control	GHMT PVP - Level 1
Chemical continuance	Good resistance to oil, petrol, acid and leach, Conform to RoHS and REACH

Part number	Number of fibres	Fire load (approx.)	Outer Ø approx.	Weight
LKD8AC30T060000	2 x 12	3.38 MJ/m	12.5 mm	155 kg/km

FELTEN Wire and Cable Solutions BV reserves the right to make changes to the product described in this specification without prior notice. FELTEN does not assume any liability which may occur due to the use of the specification described herein. Drawings are not to scale unless otherwise specified and are provided for general and informational purposes only. All values represented in this specification should be used as a guide only and exact product details can be confirmed at point of enquiry.