

GigaLine[®] I-B(ZN)BH B2ca

Indoor cable, stranded dry loose tube, 3000 N

4 x 12 G50/125/250 OM3




Illustration similar

Description

Fibre optic indoor cable, stranded dry tube, with non-metallic rodent protection.

Properties / applications

Indoor cable for fixed installation.

Suitable for data center cabling and for the use in generic cabling acc. to ISO/IEC 11801 and EN 50173. Ideally suited for all applications of Classes OF 300 to OF 10000 (depending on the fiber). Especially suitable for mounting of distribution heads für pre-assembled trunks and for splicing technology.

Laying

For indoor installation in conduits, tubes or on cable trays.

Construction

Fiber colours	IEC 60304: Fiber 1-12: Red, green, blue, yellow, white, grey, brown, violet, turquoise, black, orange, pink. Fiber 13-24: Red, green, blue, yellow, white, grey, brown, violet, turquoise, transparent, orange, pinke, each with black ring marking, except transparent.
Tube type	Stranded dry loose tube
Core colours	1st tube red, 2nd white, others green (50/125)
Strain relief (in total)	Non metallic, glass rovings
Outer sheath	Halogen free flame retardant compound (LS0H)
Colour	Lightgreen
Cable marking	KERPEN DATACOM GmbH GigaLine I-B(ZN)BH \$Abmessung\$ \$Fasertyp \$ \$Adertyp\$ 3000 N \$2xWechselstromsymbol\$ B2ca s1a d1 a1 DoP: CDESK0000095 \$BA-Nr.\$ \$Trommelnr.\$ \$m-sign. \$

GigaLine[®] I-B(ZN)BH B2ca

Indoor cable, stranded dry loose tube, 3000 N

4 x 12 G50/125/250 OM3

Optical characteristics

Category	OM3
Fiber type	G50/125/250
Bandwidth	@ 850 nm 1500 MHz x km @ 1300nm 500 MHz x km
Laser bandwidth	@ 850 nm min. 2,000 MHz x km
Attenuation	@ 850 nm max. 2.5 dB/km @ 1300nm max. 0.7 dB/km

Mechanical characteristics (cable)

Bending radius (static) (min.)	10x outer-Ø
Bending radius (dynamic) (min.)	15x outer-Ø
Max. strain relief	3000 N
Crush resistance (long term)	1000 N/100mm

Thermal characteristics (cable)

Temperature (transport / storage)	-25 °C up to +70 °C
Temperature during installation	-5 °C up to +50 °C
Temperature after installation	-10 °C up to +70 °C

Standards, certificates and approvals

Fibre standard	ISO/IEC 11801 OM3 ITU-T G651 IEC 60793-2 A1a.2
Cabling standard	EN 50173 ISO/IEC 11801
Fire class	B2ca -s1a,d1,a1
DoP	CDESK0000095
Flame retardancy	IEC 60332-1-2, IEC 60332-3-22 Cat. A
Halogen-free	IEC 60754-1
Acidity	IEC 60754-2
Smoke density	IEC 61034-1
Conformity	to CPR (EU/305/2011)
Chemical continuance	Conform to RoHS and REACH

Part number	Number of fibres	Fire load (approx.)	Outer Ø approx.	Weight
LKD8IA5BQ080000	4 x 12	0.78 MJ/m	8.3 mm	75 kg/km

FELTEN Wire and Cable Solutions BV reserves the right to make changes to the product described in this specification without prior notice. FELTEN does not assume any liability which may occur due to the use of the specification described herein. Drawings are not to scale unless otherwise specified and are provided for general and informational purposes only. All values represented in this specification should be used as a guide only and exact product details can be confirmed at point of enquiry.