

GigaLine[®] U-D(ZN)BH CI Dca

Universal cable, with circuit integrity 90 min., 2500 N

1 x 6 E9/125/250 OS2 G652.D/G657.A1



Illustration similar

Description

Fibre optic universal cable with central jelly filled loose tube, with non-metallic rodent protection and CI. Inner fire barrier. Fire protection tape made of woven glass. The cable is completely metal-free and non-conductive (dielectric).

Properties / applications

Universal cable with CI 90 min for fixed installation.
 Circuit integrity test acc. to IEC 60331-11 / IEC 60331-25 (750°C, 90 min)
 max. change of attenuation 2.0 dB
 (VDE test report 111100-9020-0001/11291)
 Resistance to fire for use in emergency circuits test acc. to EN 50200:2015 (830 +40/-0°C, 180 min)
 max. change of attenuation
 Single Mode
 max. 1.0 dB at 1310 nm und 1550 nm
 (VDE test reports:
 5005019-9601-0001/249341-TL6-1
 Date: 2018-07-20
 5005019-9601-0001/257978-TL6-1
 Date: 2019-12-20)

Suitable for campus/ backbone cabling and for the use in generic cabling acc. to ISO/IEC 11801 and EN 50173. Ideally suited for all applications of Classes OF 300 to OF 10000 (depending on the fiber). Building entries without additional transition points (splices) possible.

Laying

Indoor and outdoor installation in dry conduits, on covered cable trays. For automated cable pulling with cable winches the use of tensile-force-recording equipment is obligatory.

Construction

Fiber colours	IEC 60304: Fiber 1-12: Red, green, blue, yellow, white, grey, brown, violet, turquoise, black, orange, pink. Fiber 13-24: Red, green, blue, yellow, white, grey, brown, violet, turquoise, transparent, orange, pink, each with black ring marking, except transparent.
Tube type	Central filled loose tube
Core colours	yellow
Strain relief (in total)	Non metallic, glass rovings
Outer sheath	Halogen free flame retardant compound (LS0H)
Colour	Colza yellow
Cable marking	KERPEN DATACOM GmbH GigaLine fire secured U-D(ZN)BH 1x 6 E9/125 OS2 2500 N \$2xWechselstromsymbol\$ Dca s2 d2 a1 DoP: CDESK0000082 \$BA-Nr.\$ \$m-sign.\$

GigaLine[®] U-D(ZN)BH CI Dca

Universal cable, with circuit integrity 90 min., 2500 N

1 x 6 E9/125/250 OS2 G652.D/G657.A1

Optical characteristics

Category	OS2 G652.D/G657.A1
Fiber type	E9/125/250
Dispersion	@ 1310 nm max. 3.5 ps/(nm x km) @ 1550 nm max. 18 ps/(nm x km)
Attenuation	@ 1310 nm max. 0.36 dB/km @ 1383 nm max. 0.36 dB/km @ 1550 nm max. 0.22 dB/km @ 1625 nm max. 0.22 dB/km

Mechanical characteristics (cable)

Bending radius (static) (min.)	15x outer-Ø
Bending radius (dynamic) (min.)	20x outer-Ø
Max. strain relief	2500 N
Crush resistance (short term)	4500 N/100mm
Crush resistance (long term)	3000 N/100mm

Thermal characteristics (cable)

Temperature (transport / storage)	-25 °C up to +70 °C
Temperature during installation	-5 °C up to +50 °C
Temperature after installation	-25 °C up to +60 °C

Standards, certificates and approvals

Fibre standard	ISO/IEC 11801 OS2 ITU-T G652.D ITU-T G657.A1 IEC 60793-2 B1.3
Cabling standard	EN 50173 ISO/IEC 11801
Fire class	Dca -s2,d2,a1
DoP	CDESK0000082
Flame retardancy	IEC 60332-1-2, IEC 60332-3-22 Cat. A
Halogen-free	IEC 60754-1
Smoke density	IEC 61034-1
Conformity	to CPR (EU/305/2011)
Chemical continuance	Conform to RoHS and REACH

Part number	Number of fibres	Fire load (approx.)	Outer Ø approx.	Weight
LKD8UC700B30000	1 x 6	1.03 MJ/m	10.3 mm	115 kg/km

FELTEN Wire and Cable Solutions BV reserves the right to make changes to the product described in this specification without prior notice. FELTEN does not assume any liability which may occur due to the use of the specification described herein. Drawings are not to scale unless otherwise specified and are provided for general and informational purposes only. All values represented in this specification should be used as a guide only and exact product details can be confirmed at point of enquiry.

Forwarding to third parties only with the approval of KERPEN DATACOM GmbH
We reserve the right to make technical modifications: typographical errors and mistakes excepted.

FELTEN Wire & Cable Solutions BV

Habraken 2401
5507 TM Veldhoven
The Netherlands

www.feltenwcs.com
email: sales@feltenwcs.com
phone: +31(0)40-8200950

Number: LKD8UC700B30000
Up-dating K: 12.12.2023
Up-dating F: 18.01.2024